

Learning Deep Low-Dimensional Models from High-Dimensional Data: From Theory to Practice

Lecture 2-2: Emergence of Low-dimensional Representations in Deep Models

Zhihui Zhu

The Ohio State University

Oct 19, 2025, ICCV




THE OHIO STATE
UNIVERSITY

This Tutorial: The Outline

- Session I: Introduction of Basic Low-dimensional Models
- Session II: Understanding Low-Dimensional Structures in Representation Learning
 - Lec 2.1: Bridging Symbolic Abstraction and Low-Dimensionality in Machine Reasoning: Algebraic and Geometric Perspectives
 - **Lec 2.2: Emergency of Low-dimensional Representations in Deep Models**
- Session III: Understanding Low-Dimensional Structures in Diffusion Generative Models
 - Lec 3.1: Low-Dimensional Models for Understanding Generalization in Diffusion Models
 - Lec 3.2: Explore Low-Dimensional Structures for Constrained and Controllable Diffusion Models in Scientific Applications
- Session IV: Designing Deep Networks for Pursuing Low-Dimensional Structures
 - Lec 4.1: ReduNet: A White-box Deep Network from the Principle of Maximizing Rate Reduction
 - Lec 4.2: White-Box Transformers via Sparse Rate Reduction
- Session V: Panel Discussion: Sara Fridovich-Keil, Berivan Isik, Vladimir Pavlovic


Classical Low-dimension Model: GPCA

- Generalized PCA for mixture of subspaces [Vidal, Ma, Sastry 2005]




Modern (Deep) Representation Learning

Understand and interact with the physical world $\Rightarrow$ *nonlinear data*
Coping with nonlinearity demands (*deeper*) *representation*




Modern (Deep) Representation Learning



- Deep learning builds multiple level of abstractions
 - Learn representation from data by back-propagation
 - Reduce domain knowledge and feature engineering
 - Progressively “*linearize*” the nonlinear structure

The objective of learning:


Transform **nonlinear and complex** data to a **linear, compact, and structured** representation.



- Empirically observe across many architectures and dataset
- Theoretically justify for a simple model
- Lead to principled ways for designing architectures to pursue Low-D structures ([see Session IV, afternoon](#))

The effect of depth:

Progressively transform a nonlinear and complex distribution to a linear, compact and structured one




- Empirically observe across many architectures and dataset
- Theoretically justify for simplified models or geodesic curve connecting the two probability distributions
- Lead to principled ways for designing architectures to pursue Low-D structures

Outline

- Low-D representation in Deep Classifiers:


- Neural Collapse (NC) Phenomena
- Understanding NC from optimization
- Progressive NC and transferability



- Low-D representation in Generative Models (MLLM)


- Compression-to-Expression Phenomena

- Conclusion



Multi-Class Image Classification Problems

- Labels: $k = 1, \dots, K$
 - $K = 10$ classes (MNIST, CIFAR10, etc.)
 - $K = 1000$ classes (ImageNet)




Cat	Dog	...	Truck
$\begin{bmatrix} 1 \\ 0 \\ \vdots \\ 0 \end{bmatrix}$	$\begin{bmatrix} 0 \\ 1 \\ \vdots \\ 0 \end{bmatrix}$		$\begin{bmatrix} 0 \\ 0 \\ \vdots \\ 1 \end{bmatrix}$

One-hot labeling vectors in $\mathbb{R}^K$

- Assume balanced dataset where each class has n training samples


Deep Neural Network Classifiers




- Training a deep neural network

$$\min_{\theta', W, b} \frac{1}{Kn} \sum_{k=1}^K \sum_{i=1}^n \mathcal{L}_{\text{CE}}(W \phi_{\theta'}(x_{k,i}) + b, y_k)$$


Features (dim = 3) of CIFAR10 learned by ResNet18



Initialization



middle stage



final stage

Representation: Neural Collapse

- Characterize the geometry of representations for data separation
- [Papayan et al. 20] reveals common outcome of learned features (output of *last-hidden* layer) and classifiers across a variety of architectures and dataset
- Precise mathematical structure within the features and classifier

Prevalence of neural collapse during the terminal phase of deep learning training


Vardan Papayan, X. Y. Han, and David L. Donoho

[+ See all authors and affiliations](#)

PNAS October 6, 2020 117 (40) 24652-24663; first published September 21, 2020;

<https://doi.org/10.1073/pnas.2015509117>


Contributed by David L. Donoho, August 18, 2020 (sent for review July 22, 2020; reviewed by Helmut Boelsckei and Stéphane Mallat)



Neural Collapse: Symmetry and Structures

- **Within-Class Variability Collapse (NC1)**: features of each class collapse to class-mean with zero variability (low-dimensional features):




$$k\text{-th class, } i\text{-th sample} : \mathbf{h}_{k,i} \rightarrow \bar{\mathbf{h}}_k$$



Neural Collapse: Symmetry and Structures

- **Convergence to Simplex ETF (NC2)**: the class means are linearly separable, have same length, and maximal angle between each other:

$$\frac{\langle \bar{\mathbf{h}}_k, \bar{\mathbf{h}}_{k'} \rangle}{\|\bar{\mathbf{h}}_k\| \|\bar{\mathbf{h}}_{k'}\|} \rightarrow \begin{cases} 1, & k = k' \\ -\frac{1}{K-1}, & k \neq k' \end{cases}$$




Neural Collapse: Symmetry and Structures

- **Convergence to Self-Duality (NC3)**: the last-layer classifiers are perfectly matched with the class-means of features:

$$\frac{\mathbf{w}_k}{\|\mathbf{w}_k\|} \rightarrow \frac{\mathbf{h}_k}{\|\bar{\mathbf{h}}_k\|},$$

where $\mathbf{w}_k$ represents the k -th row of $\mathbf{W}$




Why Neural Collapse

- NC is preferred among every successful exercise in feature engineering
 - Information Theory: Simplex ETF is the optimal Shannon code
 - Classification: Simple ETF features $\Rightarrow$ Simplex ETF max-margin classifier

Question: Given the prevalence of Neural Collapse across datasets and network architectures, why would such a phenomenon happen in training overparameterized networks?


Dealing with a Highly Nonconvex Problem




$$\min_{\theta', W, b} \frac{1}{Kn} \sum_{k=1}^K \sum_{i=1}^n \mathcal{L}_{\text{CE}}(W \phi_{\theta'}(x_{k,i}) + b, y_k) + \lambda \|(\theta', W, b)\|_F^2$$

The problem is highly nonconvex [Li et al'18]

- Nonlinear interactions across layers
- Nonlinear activation functions



Simplification: Unconstrained Features



$$\min_{\theta', W, b} \frac{1}{Kn} \sum_{k=1}^K \sum_{i=1}^n \mathcal{L}_{\text{CE}}(W \phi_{\theta'}(\mathbf{x}_{k,i}) + \mathbf{b}, \mathbf{y}_k) + \lambda \|(\theta', W, b)\|_F^2$$

- Assumption

Treat $\mathbf{h}_{k,i} = \phi_{\theta'}(\mathbf{x}_{k,i})$ as a **free** optimization variable

Unconstrained features model
[Mixon et al'20]



$$\min_{H, W, b} \frac{1}{Kn} \sum_{k=1}^K \sum_{i=1}^n \mathcal{L}_{\text{CE}}(W \mathbf{h}_{k,i} + \mathbf{b}, \mathbf{y}_k) + \lambda \|(\mathbf{H}, W, b)\|_F^2$$

where $\mathbf{H} := [\mathbf{h}_{1,1} \quad \cdots \quad \mathbf{h}_{K,n}]$

Heavy Parameterization in CV Models

IMAGENET

- 1000 object classes
- Images:
 - 1.2 M train
 - 100K test




ImageNet Classification Leaderboard from paperswithcode.com

Performance & Model size keep **increasing**

parameters >> # training samples

Simplification: Unconstrained Features




$$\min_{\mathbf{H}, \mathbf{W}, \mathbf{b}} \frac{1}{Kn} \sum_{k=1}^K \sum_{i=1}^n \mathcal{L}_{\text{CE}}(\mathbf{W} \mathbf{h}_{k,i} + \mathbf{b}, \mathbf{y}_k) + \lambda \|(\mathbf{H}, \mathbf{W}, \mathbf{b})\|_F^2$$

- **Validity:** Modern networks are highly **overparameterized**, that can approximate any point in the feature space
 - also called **Layer-peeled model** [Fang et al'21] and has been widely used recently for studying NC

J. Lu and S. Steinerberger, Neural collapse with cross-entropy loss, ACHA, 2022
W. E and S. Wojtowytsch, On the emergence of tetrahedral symmetry in the final and penultimate layers of neural network classifiers, 2021
D. Mixon, H. Parshall, J. Pi. Neural collapse with unconstrained features, 2020
C. Fang, H. He, Q. Long, W. Su, Layer-peeled model: Toward understanding well-trained deep neural networks, 2021
W. Ji, Y. Lu, Y. Zhang, Z. Deng, W. Su, An unconstrained layer-peeled perspective on neural collapse, 2021
J. Zarka, F. Guth, S. Mallat, Separation and Concentration in Deep Networks, ICLR, 2021.
F. Graf, C. Hofer, M. Niethammer, R. Kwitt, Dissecting Supervised Contrastive Learning, ICML, 2021.
T. Ergen, M. Pilanci, Revealing the structure of deep neural networks via convex duality, ICML, 2021.
A Rangamani, M Xu, A Banburski, Q Liao, T Poggio, Dynamics and Neural Collapse in Deep Classifiers trained with the Square Loss. 2021.

Experiment: NC Occurs on Random Labels/Inputs

- CIFAR-10 Dataset with **random** labels, MLP with **varying network width**



- **Validity of unconstrained features model:** Learned last-layer features and classifiers seems to be independent of input!
- The network memorizes training data in a very special way: NC
- We observe similar results on **random** inputs (**random** pixels)

Geometric Analysis of Global Landscape

$$\min_{\mathbf{H}, \mathbf{W}, \mathbf{b}} \frac{1}{Kn} \sum_{k=1}^K \sum_{i=1}^n \mathcal{L}_{\text{CE}}(\mathbf{W} \mathbf{h}_{k,i} + \mathbf{b}, \mathbf{y}_k) + \lambda \|(\mathbf{H}, \mathbf{W}, \mathbf{b})\|_F^2$$

Theorem (informal) Let feature dim $d \geq \text{\#class } K-1$.

(Global Optimality) Any global solution $(\mathbf{W}^*, \mathbf{H}^*, \mathbf{b}^*)$ must satisfy NC: $\mathbf{b}^* = \mathbf{0}$ and

$$\underbrace{\mathbf{h}_{k,i}^* = \bar{\mathbf{h}}_k}_{NC_1}, \quad \underbrace{\frac{\langle \bar{\mathbf{h}}_k^*, \bar{\mathbf{h}}_{k'}^* \rangle}{\|\bar{\mathbf{h}}_k^*\| \|\bar{\mathbf{h}}_{k'}^*\|} = \begin{cases} 1, & k = k' \\ -\frac{1}{K-1}, & k \neq k' \end{cases}}_{NC_2}, \quad \underbrace{\frac{\mathbf{w}^{k*}}{\|\mathbf{w}^{k*}\|} \rightarrow \frac{\bar{\mathbf{h}}_k^*}{\|\bar{\mathbf{h}}_k^*\|}}_{NC_3}$$

- $d \geq K-1$ is required to make K class-mean features equal angle with cosine angle $-\frac{1}{K-1}$ (the largest possible) between each pair.
- The features have zero global mean
- If H are constrained to be nonnegative (output of ReLu unit)
 - Bias term compensates for the global mean of the features $\mathbf{b} \rightarrow -\mathbf{W} \mathbf{h}_G$

Geometric Analysis of Global Landscape

- [Lu et al.'22] studies the following one-example-per class model

$$\min_{\mathbf{H}} \frac{1}{K} \sum_{k=1}^K \mathcal{L}_{\text{CE}}(\mathbf{h}_k, \mathbf{y}_k), \text{ s. t. } \|\mathbf{h}_k\|_2 = 1$$

- [E et al.'21, Fang et al.'21, Gral et al.'21] studies constrained formulation

$$\min_{\mathbf{W}, \mathbf{H}} \frac{1}{Kn} \sum_{k=1}^K \sum_{i=1}^n \mathcal{L}_{\text{CE}}(\mathbf{W} \mathbf{h}_{k,i}, \mathbf{y}_k), \text{ s. t. } \|\mathbf{W}\|_F^2 \leq C_W, \|\mathbf{H}\|_F^2 \leq C_H$$

- These work show that any **global** solution has NC, but
 - What about **local minima**?
 - The constraint formulations are not aligned with practice

J. Lu and S. Steinerberger, Neural collapse with cross-entropy loss, ACHA, 2022

W. E and S. Wojtowytsch, On the emergence of tetrahedral symmetry in the final and penultimate layers of neural network classifiers, 2021

D. Mixon, H. Parshall, J. Pi. Neural collapse with unconstrained features, 2020

C. Fang, H. He, Q. Long, W. Su, Layer-peeled model: Toward understanding well-trained deep neural networks, 2021

W. Ji, Y. Lu, Y. Zhang, Z. Deng, W. Su, An unconstrained layer-peeled perspective on neural collapse, 2021

J. Zarka, F. Guth, S. Mallat, Separation and Concentration in Deep Networks, ICLR, 2021.

F. Graf, C. Hofer, M. Niethammer, R. Kwitt, Dissecting Supervised Contrastive Learning, ICML, 2021.

T. Ergen, M. Pilanci, Revealing the structure of deep neural networks via convex duality, ICML, 2021.


A Rangamani, M Xu, A Banburski, Q Liao, T Poggio, Dynamics and Neural Collapse in Deep Classifiers trained with the Square Loss, 2021.

Geometric Analysis of Global Landscape

$$\min_{\mathbf{H}, \mathbf{W}, \mathbf{b}} \frac{1}{Kn} \sum_{k=1}^K \sum_{i=1}^n \mathcal{L}_{\text{CE}}(\mathbf{W} \mathbf{h}_{k,i} + \mathbf{b}, \mathbf{y}_k) + \lambda \|(\mathbf{H}, \mathbf{W}, \mathbf{b})\|_F^2$$

Theorem (informal) Let feature dim $d \geq \text{\#class } K-1$.

(Benign Global Landscape) The function has no spurious local minimizer and is a strict saddle function, with negative curvature for non-global critical points.



General nonconvex problems

Our training problem

NC always Happens


$$\min_{H, \mathbf{W}, \mathbf{b}} \frac{1}{Kn} \sum_{k=1}^K \sum_{i=1}^n \mathcal{L}_{\text{CE}}(\mathbf{W} \mathbf{h}_{k,i} + \mathbf{b}, \mathbf{y}_k)$$

Theorem (informal) (Global Optimality) Any global solution must satisfy NC
(Benign Global Landscape) The loss has no spurious local minimizer and is a strict saddle function, with negative curvature for non-global critical point.


Message: deep networks always learn Neural Collapse features and classifiers

Experiment: NC is Algorithm Independent


- ResNet18 on CIFAR-10 with **different training algorithms**



Within-Class Variability (NC1)



Between-Class Separation (NC2)



Self-Duality Collapse (NC3)

- The smaller the quantities, the severer NC
- NC across **different training algorithms**

NC always Happens

$$\min_{H, \mathbf{W}, \mathbf{b}} \frac{1}{Kn} \sum_{k=1}^K \sum_{i=1}^n \mathcal{L}_{\text{CE}}(\mathbf{W} \mathbf{h}_{k,i} + \mathbf{b}, \mathbf{y}_k)$$

Theorem (informal) (Global Optimality) Any global solution must satisfy NC
(Benign Global Landscape) The loss has no spurious local minimizer and is a strict saddle function, with negative curvature for non-global critical point.

Message: deep networks always learn Neural Collapse features and classifiers

- Holds for many other losses, such as focal, label smoothing, MSE
 - all losses lead to largely identical features on training data and performance on testing
- Analysis can be extended to understand other training paradigms, such as MCR², self-supervised, etc.

All Losses Lead to Identical Features?

- We study them under the unconstrained feature model:

$$\min_{\mathbf{H}, \mathbf{W}, \mathbf{b}} \frac{1}{Kn} \sum_{k=1}^K \sum_{i=1}^n \mathcal{L}(\mathbf{W} \mathbf{h}_{k,i} + \mathbf{b}, \mathbf{y}_k) + \lambda \|(\mathbf{H}, \mathbf{W}, \mathbf{b})\|_F^2$$


Theorem (informal) With feature dimension feature dim $d \geq \text{\#class } K-1$, the losses (CE, FL, LS, MSE, etc) lead to the same NC features and classifiers

Implication for practical network: If network is large enough and trained longer enough

- All losses lead to largely identical features on **training data** (NC)
- All losses lead to largely identical performance on **test data**

Experiments: Different Losses on CIFAR10

- ResNet50, CIFAR-10 with different network width and training epoches




- Left bottom corner has **larger** difference than right top corner
- If network is large enough and trained longer enough:
 - All losses lead to largely identical features on training data (NC)
 - All losses lead to largely identical performance on test data

Exploit NC for Practical Network Training


Observation: NC is prevalent, and classifier always converges to a Simplex ETF

- **Implication 1: No need to learn the classifier**
 - Just fix it as a Simplex ETF
 - Save 8%, 12%, and 53% parameters for ResNet50, DenseNet169, and ShuffleNet!
- **Implication 2: No need of large feature dimension d**
 - Just use feature dim $d = \text{\#class } K$ (e.g., $d=10$ for CIFAR10)
 - Further saves 21% and 4.5% parameters for ResNet18 and ResNet50!



Experiment: Fixed Classifier with $d = K$

- ResNet50 on CIFAR10 with different settings
 - Learned classifier (default) **VS** fixed classifier as a simplex ETF
 - Feature dim $d = 2048$ (default) **VS** $d = 10$




- Training with **small** dimensional features and **fixed** classifiers achieves **on-par performance** with **large** dimensional features and **learned** classifiers.

Related Work on NC

- A **non-comprehensive** overview of related work on NC
 - Theoretical analysis of NC
 - Unconstrained features model (UFM)
 - Deep unconstrained features model [Tirer & Bruna'22, Súkeník et al.'24]
 - Beyond UFM
 - global optimality [Jacot et al.'24]
 - gradient flow analysis [Min et al.'25]
 - Loss design
 - CE loss
 - MSE loss [Han et al.'22, Zhou et al.'22]
 - Supervised contrastive [Graf et al.'21]
 - Multi-label learning [Li et al.'24]
 - Large number of classes [Liu et al.'23]
 - **Progressive NC** [Wang et al.'23]
 - Applications for understanding & improving network performance
 - Efficient training
 - **Transfer learning** [Galanti et al.'22, Li et al.'24]
 - Imbalanced learning [Fang et al.'21]
 - Continual learning [Yang et al.'23]
 - Differential privacy [Wang et al.'24]
 - Robustness [Su et al.'23]
 - Generalization [Hui et al.'22]
 - Feature learning in intermediate layers [He & Su'23, Rangamani et al.'23]
 - LLM [Wu'24]



Implications on Transfer Learning



- Why transfer learning is possible
- How to improve transfer learning performance
 - initialization for the new classifier
 - efficient fine-tuning

Experiment: Fixed Classifier as Class-mean Features

- We can also promote NC3 (self-duality) by fixing the *classifier* as the *class-mean features* (CMF) during training




- CMF achieves **on-par performance** with **learned** classifiers

Experiment: Fixed Classifier as Class-mean Features

- CMF classifier improves Out-of-distribution (OOD) performance for fine-tuning

- ResNet50 pretrained on MoCo
- Fine-tuned for CIFAR10



- Since self-duality (NC3) always hold, CMF classifier can better preserve properties of pretrained model during fine-tuning


Progressive separation from shallow to deep layers

- From shallow to deep layers (effect of depths): progressive compression and separation

Layer 1





Layer 2



Layer 4



Layer 6



- Effect of depth: creates progressive separation and collapse


He, Hangfeng, and Weijie J. Su. "A law of data separation in deep learning," PNAS 2023.

Wang, Li, Yaros, Hu, Zhu, , Balzano, Qu, Understanding Deep Representation Learning via Layerwise Feature Compression and Discrimination, JMLR 2025


Jinxin Zhou, Jiachen Jiang, Zhihui Zhu, Are all layers created equal: A neural collapse perspective, CPAL 2025.

Are all Layers Created Equal?

- Scaling up the model makes middle layers redundant
- Deeper layers excel at enhancing neural collapse (prone to memorization); other layers are good for transfer learning




CIFAR10



ImageNet


Progressive Separation is Transferable

- Progressive separation is transferable among different tasks (common in medical domain)
 - ResNet-34 pre-trained on ImageNet
 - Evaluate on CIFAR10
 - Model is fixed without fine-tuning
 - Train a linear classifier on top of the features
- Layer-wise NC exhibits two phases on downstream tasks:
 - Phase 1: progressively decreasing (universal feature mapping)
 - Phase 2: progressively increasing (specific feature mapping) **fine-tune this layer!**




Efficient Layer Fine-tuning

Fine-tuning one key intermediate layer is sufficient




(a) Illustration of layer fine-tuning



(b) Fine-tuning results on CIFAR-10

The objective of learning:
Transform **nonlinear and complex** data to
a **linear, compact, and structured** representation.




The effect of depth:
Progressively achieve this goal through layer-wise transformation

Outline

- Low-D representation in Deep Classifiers:


- Neural Collapse (NC) Phenomena
- Understanding NC from optimization
- Progressive NC and transferability



- Low-D representation in Generative Models (LLM)

- Compression-to-Expression Phenomena

- Conclusion



Generative Models

Two popular and effective approaches to learn distribution $P(x_1, x_2, \dots, x_n)$

- diffusion model (see Session III by Liyue and Qing, afternoon)
- autoregressive model: $P(x_1)P(x_2|x_1) \dots P(x_n|x_1, \dots, x_{n-1})$

ChatGPT >



x : prompt → what is in-context learning

- Natural language conversation

$$P(y|x)$$

← y : response

In-context learning is when a model (like GPT) learns to perform a task *just by seeing examples of it inside the prompt*, without changing its underlying weights.

For example:

- You give the model a few examples of English-to-French translations ("dog → chien", "cat → chat") in the prompt.
- Then you ask it to translate "house → ?"
- The model "learns" from the pattern in the prompt and answers correctly ("maison"), **without** any retraining or updating.

It's like a model is **reading a mini-lesson** on-the-fly and **figuring out** what to do, based only on what it sees.


This is very different from traditional supervised learning, where you fine-tune a model with gradient descent.

Would you like a simple diagram too? 📖✨

In-context Learning

- LLM can “learn” to solve tasks without weight updates

ChatGPT >



A = 3, B = 1, C = 4, D = 1, E = 5, F =

ChatGPT >



A = 3, B = 1, C = 4, D = 1, E = 5, F =

It looks like you're listing letters with corresponding numbers:

A = 3, B = 1, C = 4, D = 1, E = 5, and now you're asking for F = ?

From the numbers 3, 1, 4, 1, 5... this sequence looks familiar — it's the beginning of the digits of π (**pi**): 3.1415...

Following that logic, the next digit of π after 3.1415 is **9**.

Letter Prediction Tasks

Prompt: a → b, b → c, g → h, m → n

Diagram labels: "paired demonstrations" spans the first three pairs (a→b, b→c, g→h). "query" spans the pair (m→). "answer" spans the letter n.


Prompt: a → c, b → d, g → l, m → o

Prompt: a → a, b → b, g → g, m → m

Prompt: a → B, b → C, g → H, m → N

- Step 1: identify the “rule/task/pattern” from the demonstrations
- Step 2: apply it to the query token “m”
- Does the LLM perform ICL in the same way?

In-context Learning



- Step 1: identify the “rule/task/pattern” from the demonstrations
- Step 2: apply it to the query token
- Does the MLLM perform ICL in the same way?


How Do LLM Perform ICL

- The models are only pre-trained to predict next token. Why can they learn the input-output relationship in the prompt?
- Different approaches for understanding the ICL ability
 - Bayesian Perspective [Xie et al., 2021]
 - Meta-learning Perspective [Chen et al., 2021]
 - Meta-optimizer perspective [Oswald et al 2022, Ahn et al, 2023]
 - Mechanistic Interpretations (induction heads in copy problems [Olsson et al., 2022])
 - etc.
- But less emphasis on the internal representations within models

How do MLLMs extract and differentiate task information from shallow to deep layers during in-context learning?

Tracing Hidden Representation

- Study layer-wise representations



- Denote the hidden representation of the last token at layer l as $h^{(l)}$, known as task vector or in-context vector

Metric for Compression & Discrimination

- For each ICL task t (e.g. next letter prediction), generate N prompts

Prompt 1: $a \rightarrow b, b \rightarrow c, c \rightarrow d, d \rightarrow$  $\mathbf{h}_{1,t}^{(l)}$

Prompt 2: $d \rightarrow e, l \rightarrow m, s \rightarrow t, u \rightarrow$  $\mathbf{h}_{2,t}^{(l)}$

...

Prompt N : $m \rightarrow n, f \rightarrow g, i \rightarrow j, k \rightarrow$  $\mathbf{h}_{N,t}^{(l)}$

- Define mean vector and variance

$$\bar{\mathbf{h}}_t^{(\ell)} = \frac{1}{N} \sum_{i=1}^N \mathbf{h}_{i,t}^{(\ell)} \quad \text{var}_t^{(\ell)} = \frac{1}{N} \sum_{i=1}^N \left\| \mathbf{h}_{i,t}^{(\ell)} - \bar{\mathbf{h}}_t^{(\ell)} \right\|_2^2$$

Metric for Compression & Discrimination

- **TDNV** (Task-Distance Normalized Variance) to capture the level of compression and separation

$$\text{TDNV}^{(\ell)} = \sum_{t \neq t'} \frac{\text{var}_t^{(\ell)} + \text{var}_{t'}^{(\ell)}}{\left\| \bar{\mathbf{h}}_t^{(\ell)} - \bar{\mathbf{h}}_{t'}^{(\ell)} \right\|_2^2}$$


- **Within-task Variance**: how well the representation from the same task are **compressed** towards its own task mean
- **Between-task Distance**: how well the task means of different task are **discriminated** from each other

From Compression to Expression/Expansion

Progressive **compression** and then **expression** from shallow layers to deep layers

Task Groups	Task	Example
Letter-to-Letter	Copy Letter	$a \rightarrow a$
	Next Letter	$a \rightarrow b$
	To Uppercase	$a \rightarrow A$
	Prev Letter	$b \rightarrow a$
	Next 2 Letter	$a \rightarrow c$


Algorithmic Tasks



- **Compression phase**: the model produces compact & discriminative representation that captures the “rule/task/pattern” from the input data
- **Expression phase**: apply the compact representation to the input query

Prevalence of the Phenomenon

Universality across model architectures (Transformer & State-Space Model)




Prevalence of the Phenomenon

Universality across task domains

Symbolic ICL (Beyond Algorithmic)


Translation	French → English	bonjour → hello
	Spanish → English	gracias → thank you
	English → French	goodbye → au revoir
	English → Italian	music → musica
	English → Spanish	thank you → gracias
Linguistic	Antonyms	hot → cold
	Plural → Singular	cats → cat
	Present Simple → Gerund	run → running
	Present Simple → Past Perfect	walk → had walked
	Present Simple → Past Simple	jump → jumped
	Singular → Plural	dog → dogs
Knowledge	Country → Capital	France → Paris
	Football Player → Position	Lionel Messi → Forward
	Location → Continent	Brazil → South America
	Location → Country	Kyoto → Japan
	Location → Language	Egypt → Arabic
	Location → Religion	India → Hinduism




Prevalence of the Phenomenon

Universality across task domains

Multimodality ICL (Beyond Language)


image	color	shape	size	texture
	yellow	triangle	small	solid
	blue	square	large	dots
	red	star	large	solid
	black	pentagon	large	checker
	green	circle	small	stripes

Attribute	Labels
Color	red, green, blue, yellow, black
Shape	circle, square, triangle, pentagon, star
Size	small, medium, large
Texture	solid, stripes, dots, checker



Compression-Expression Emerges During Training



Emergence during training



- Before training: flat TDNV values across all layers
- During training: distinct U-shape curve emerges and deepens

Scaling Model Promotes Compression


Scaling up model size leads to more compressed representations



Compressed level correlates with the ICL performance.


Number of Demonstrations Promotes Compression

Increasing in-context lengths (num of demonstrations K) leads to more compressed representations.



Bias-variance Decomposition

- Different tasks induce task vectors in distinct directions, yet each task follows a consistent direction
- The variance within each task decreases




$$\mathbf{h}_{i,t}(K) = \underbrace{\mu_t(\infty)}_{\text{ideal representation}} + \underbrace{\mu_t(K) - \mu_t(\infty)}_{\text{bias}} + \underbrace{\mathbf{h}_{i,t}(K) - \mu_t(K)}_{\text{variance}}$$

$$\mu_t(K) = \mathbb{E}_i[\mathbf{h}_{i,t}(K)]$$


$$\mu_t(\infty) = \lim_{K \rightarrow \infty} \mathbb{E}_i[\mathbf{h}_{i,t}(K)]$$

Decrease of Bias and Variance



Decrease of Bias:

$$\frac{\|\boldsymbol{\mu}_t(K) - \boldsymbol{\mu}_t(\infty)\|_2}{\|\boldsymbol{\mu}_t(0) - \boldsymbol{\mu}_t(\infty)\|_2} \propto \mathcal{O}\left(\frac{1}{K}\right)$$




Decrease of Variance:

$$\left\| \mathbb{E} \left[(\mathbf{h}_{t,i}(K) - \boldsymbol{\mu}_t(K))^2 \right] \right\|_2 \propto \mathcal{O}\left(\frac{1}{K}\right)$$

- A formal analysis for simplified models (linear attention)

Task Vector Accuracy


- Query + task-vector $h^{(l)}$ is enough to perform ICL



- How much the hidden representation captures the task information


Early Exit Accuracy

Make prediction based on **intermediate layer** hidden states instead of last layer



- How much the hidden representation captures the query information



Layerwise Compression and Expression



- The most compact representation (***smallest* TDNV**) achieves ***best* Task Vector Accuracy** (Query + task-vector $h^{(l)}$)
- **Early-exit Accuracy** starts increasing after the most compact layer



Promoting Compression Improves Performance

Task-vector contrastive fine-tuning improves task-vector accuracy



- **Method:** during fine-tuning on ICL tasks, add **contrastive loss** on intermediate layer features to encourage compression
- **Results:** more compressed representations yield better performance; task-vector accuracy improves by 20%

Linear, compact, and structured representation emerges in deep classifiers and (multimodal) large language models



The objective of learning: Transform **nonlinear and complex** data to a **linear, compact, and structured** representation.

The effect of depth: **Progressively** achieve this goal through layer-wise transformation

This Tutorial: The Outline

- Session I: Introduction of Basic Low-dimensional Models
- Session II: Understanding Low-Dimensional Structures in Representation Learning
 - Lec 2.1: Bridging Symbolic Abstraction and Low-Dimensionality in Machine Reasoning: Algebraic and Geometric Perspectives
 - **Lec 2.2: Emergency of Low-dimensional Representations in Deep Models**
- Session III: Understanding Low-Dimensional Structures in **Diffusion Generative Models** (**starts from 1PM**)
 - Lec 3.1: Low-Dimensional Models for Understanding Generalization in Diffusion Models
 - Lec 3.2: Explore Low-Dimensional Structures for Constrained and Controllable Diffusion Models in Scientific Applications
- Session IV: **Designing** Deep Networks for Pursuing Low-Dimensional Structures
 - Lec 4.1: ReduNet: A White-box Deep Network from the Principle of Maximizing Rate Reduction
 - Lec 4.2: White-Box Transformers via Sparse Rate Reduction
- Session V: Panel Discussion: Sara Fridovich-Keil, Berivan Isik, Vladimir Pavlovic